



#### Features & Benefits

- **Fast** - Laminates pressure sensitive films up to 65" (1650 mm) wide at speeds up to 16.4' (5m/min) per minute.
- **Quality**– Digital controls for temperature (RSC-1650H only) and speed help deliver a perfect finish, combined with silicone rubber rollers
- **Versatility** -Designed for mounting up to 5/8" (15mm), laminating individual or multiple copies of posters prints, POP signs, training aids, rigid or flexible signage, inkjet, photo, floor graphics and much more.
- **Easy To Use** - Simple one button operation plus standard remote control and foot pedal allow hands-free operation.
- **Convenient**– High quality silicone rubber rollers allow cold lamination for heat sensitive applications.

### 65" WIDE FORMAT COLD SERIES LAMINATOR

Model	RSC-1650C	RSC-1650H Heat Assist
Power supply	AC 120V/60Hz	
Power consumption	150W	1650W
Film thickness	1-10 (mil ) / 25-250 (mic)	
Max laminating width	65 (in) / 1650 (mm)	
Max laminating speed	16.4 (ft/min) / 5 (m/min)	
Ready time	0 min	10 min
Heating method	N/A	Hot top roller
Driving motor	DC geared motor	
Temperature control	N/A	Digital up to 122°F (50°C)
Speed control	Digital (micom) 9 settings	
Transport type	2 Roller	
Rewind for release liner	Yes	
Cross cutter	Yes	
Document guides	Yes	
Hot lamination	No	
Cold lamination	Yes	
Mounting/foam board	Yes/up to 5/8" (15mm)	
Reverse	Yes	
Remote control	Yes	
Foot pedal	Yes	
Unit Weight	551 (lbs) / 250 (kg)	
Unit Dimensions (W x D x H)	77.1 x 25.5 x 47.6 (in) 1960 x 650 x 1210 (mm)	
Carton Weight	706 (lbs) / 320 (kg)	
Carton Dimensions (W x D x H)	86 x 35 x 57.5 (in) 2184 x 888 x 1460 (mm)	
Warranty	1 year parts & labor (Rollers 6 months)	



**Have Our Plastic Inc.**  
 Have Our Plastic Inc.  
 4 - 6990 Creditview Road  
 Mississauga, ON  
 L5N 8R9  
 Canada  
 Tel: 905-821-7550  
 Fax: 905-821-7553  
 Toll Free: 1-800-263-5995 (Canada)  
 Toll Free: 1-800-567-1775 (USA)  
 E-mail: sales@hop.ca