



RSH-1151
RSH-1651



Features & Benefits

- **Fast** - Laminates pressure sensitive and thermal films up to 45" (1150mm) wide at speeds up to 9.8' (3m/min) per minute for hot lamination and 13' (4m/min) per minute for cold lamination.
- **Quality**– Digital controls for temperature and speed, combined with silicone rubber rollers help deliver a perfect finish.
- **Versatility** –Designed for mounting, laminating & encapsulating individual or multiple copies of posters prints, POP signs, training aids, rigid or flexible signage floor graphics, trade show displays and much more.
- **Convenient**– Auto-grip film shafts for easy material handling. High quality rollers allow cold lamination for heat sensitive applications.

WIDE FORMAT DUAL HOT & COLD LAMINATORS

Power supply	AC 200-240V/50-60Hz Single phase
Power consumption	3300W
Film thickness	1-10 (mil) / 25-250 (mic)
Max laminating width	45 (in) / 1150 (mm)
Max laminating speed	Hot - 9.8 (ft/min) / 3 (m/min) Cold -13 (ft./min) / 4 (m/min)
Ready time	22 min
Heating method	Hot roller (internal infrared heater)
Driving motor	DC geared motor
Temperature control	Digital up to 302°F (150°C)
Speed control	Digital (micom)
Cooling system	Blower
Auto off/Standby	Yes
Cross cutter	Yes
Side cutter	Option
Hot lamination	Yes
Cold lamination	Yes
Mounting/foam board	Yes/up to 5/8" (15mm)
Paper counter	Yes
Length measurement	Yes
Reverse	Yes
Remote control	Yes
Foot pedal	Yes
Unit Weight	375 (lbs) / 170 (kg)
Unit Dimensions (W x D x H)	55.1 x 25.5 x 47.6 (in) 1400 x 650 x 1210 (mm)
Carton Weight	529 (lbs) / 240 (kg)
Carton Dimensions (W x D x H)	61 x 35 x 57 (in) 1550 x 888 x 1447 (mm)
Warranty	1 year parts & labor (Rollers 6 months)



Have Our Plastic Inc.

Have Our Plastic Inc.
4 - 6990 Creditview Road
Mississauga, ON
L5N 8R9
Canada
Tel: 905-821-7550
Fax: 905-821-7553
Toll Free: 1-800-263-5995 (Canada)
Toll Free: 1-800-567-1775 (USA)
E-mail: sales@hop.ca