



RSL-2702



Features & Benefits

- **Fast** - Laminates thermal and pressure sensitive films up to 27" (685 mm) wide at speeds up to 8.2" (2.5m/min) per minute.
- **Versatile**– Able to mount rigid boards up to 3/16" (6mm) and laminate up to 10mil (250mic) film, including THINFLEX.
- **Flexible** -Designed for laminating, encapsulating and mounting with adjustable nip settings (max. opening 3/16"/6mm).
- **Easy To Use** - Soft touch digital keypad allows easy operation and function control of temperature, speed and stored programs.
- **Convenient**– Swing-out arm film shafts and drop down idler all in a tabletop roll laminator designed for a small working area.

27" FULL FEATURED TABLE TOP LAMINATOR

Power supply	AC120V / 60Hz
Power consumption	1500W
Max laminating width	27 (in) / 685 (mm)
Max laminating speed	8.2 (ft/min) / 2.5 (m/min)
Film thickness	1~10 (mil) / 25~250 (mic)*
Film core size	Auto grip 2.25" and 3"
Max film roll diameter	7.9"
Ready time	10 min
Heating method	Hot Roller
Driving motor	DC geared motor
Temperature control	Digital 302°F (150°C)
Speed control	Digital (9 settings)
Cooling system	2 fans
Transport type	4 Roller
Auto Off/Standby	Yes
Cross cutter	Yes
Document guides	Yes
Hot lamination	Yes
Cold lamination	Yes
Mounting/foam board	Yes 3/16" (6mm)
THINFLEX™ lamination	Yes
Reverse	Yes
Unit weight	124(lbs) / 56 (kg)
Unit dimensions (W x D x H)	38 x 21.5 x 18.5 (in) 970 x 540 x 470 (mm)
Carton weight	157 (lbs) / 71 (kg)
Carton dimensions (W x D x H)	44.5 x 24 x 23.5 (in) 1130 x 740 x 600 (mm)
Warranty	1 year parts & labor (Rollers 6 months)

*1-10 mil Royal Sovereign Films. Others Manufacturers May Vary



Have Our Plastic Inc.
 Have Our Plastic Inc.
 4 - 6990 Creditview Road
 Mississauga, ON
 L5N 8R9
 Canada
 Tel: 905-821-7550
 Fax: 905-821-7553
 Toll Free: 1-800-263-5995 (Canada)
 Toll Free: 1-800-567-1775 (USA)
 E-mail: sales@hop.ca